

PRODUCT DATA SHEET

SikaPaver® HC-218

Compaction aid for semi-dry concrete with improved mold filling properties

DESCRIPTION

SikaPaver® HC-218 is a filling and compaction aid which has been designed to eliminate the stickiness of semi-dry concretes at elevated water-cement-ratios. The resulting granular concrete leads to an even mold filling and less quality fluctuations while ensuring the targeted concrete compaction.

USES

- Concrete Pavers
- Masonry Blocks
- Roof Tiles
- Kerbstones
- Landscaping elements

CHARACTERISTICS / ADVANTAGES

- Granular mold-filling properties despite high water contents
- Even concrete distribution into the individual chambers across the compaction mold
- Less quality variations and consequently less second grade products

SikaPaver® HC-218 improves the dispersion and wetting of cement, additives and pigments and hence allows reaching the target density in shorter time or the reduction of pore content at the same compaction effort

APPROVALS / STANDARDS

Corresponds to EN 934-2 Table 5 (air entrainer).

PRODUCT INFORMATION

Chemical Base	Blend of Surfactants
Packaging	Drum: 200 kg net weight IBC: 1000 kg net weight Bulk: min 6 t
Shelf Life	12 months from date of production if stored properly in original, unopened packaging. After prolonged Storage, agitate the product before using.
Storage Conditions	Protect from frost, intense sunlight and contamination. In case of bulk delivery, the tanks and equipment used must be clean.
Appearance / Colour	liquid, colorless to yellowish
Density	1.00 kg/dm³ at +20°C
pH-Value	ca. 7
Total Chloride Ion Content	≤ 0.10 %
Equivalent Sodium Oxide	≤ 0.5 %

APPLICATION INFORMATION

PRODUCT DATA SHEET

SikaPaver® HC-218December 2022, Version 04.01
021404061000000145

Recommended Dosage	0.2 - 0.5 M% of binder (cement and fly ash)
Dispensing	SikaPaver® HC-218 shall be added with the mixing water or introduced at the end of the mixing process. The necessary mixing time after the admixture dosage depends on the individual mixer.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Pakistan (Pvt.) Limited

141-CCA Phase IV, DHA Lahore Punjab 54792 Pakistan phone: +92 42 3569 4266 - 67 fax: +92 42 3569 4268 http://pak.sika.com/

Sika Pakistan (Pvt.) Limited 141-CCA Phase IV, DHA

Lahore Punjab 54792 Pakistan phone: +92 42 3569 4266 - 67 fax: +92 42 3569 4268 http://pak.sika.com/

SikaPaverHC-218-en-PK-(12-2022)-4-1.pdf

