

Product Data Sheet
Edition 08.2010
Identification no:
02 09 02 90 100 0 000009
Sika® Reactivation Primer

Sika® Reactivation Primer

(Liquid Plastics Reactivation Primer)

One-component primer for the reactivation of existing Sikalastic® roofing systems

Product Description Single pack, polyurethane based primer for the reactivation of Sikalastic® roofing systems

Uses ■ Primer for use when recoating existing Sikalastic® MTC roofing systems and Sikafloor® balcony waterproofing systems

Characteristics / Advantages

- Strengthens adhesion to existing Sikalastic® and Sikafloor® systems
- Allows further coats to be safely applied when the standard re-coating window has been exceeded
- Suitable for use over a wide range of existing polyurethane roofing membranes (subject to satisfactory adhesion testing)
- Single pack
- Quickly and easily applied
- May be overcoated from 3 hours
- Applicable down to 5°C

Product Data

Form

Appearance / Colour Low viscosity liquid, clear

Packaging 5 litre (~5.15 kg) Container

Storage

Storage Conditions / Shelf Life 12 months from date of production if stored properly in original, unopened and undamaged sealed container. Expiry date on container.

Technical Data

Chemical Base Solvent borne polyurethane

Density ~1.03 kg/l

Flash Point 42 °C



System Information

Application Details

Consumption / Dosage	Apply in a single coat at appr. 0.1kg/m ² .
Substrate Quality	Surfaces must be clean and free from grease.
Substrate Preparation	Pre-treat with Sika® Biowash on areas subject to organic growth.

Application Conditions / Limitations

Substrate Temperature	5 °C min. / +30 °C max.
Ambient Temperature	5 °C min. / +30 °C max.
Relative Air Humidity	<85%
Dew Point	Beware of condensation! Surface temperature during application must be at least +3°C above dew point.

Application Instructions

Application Method / Tools	.Apply between 5 and 30 °C. Substrate temperatures should remain a minimum of 3°C above dew point throughout the application and curing periods. Apply by brush or roller . Use brushes for small areas only.
Cleaning of Tools	Aromatic solvent cleaners are recommended.
Potlife	Once opened, the product should be used promptly. Storage of part containers may result in performance being affected.
Waiting Time / Over coating	At 20 °C: 3-4 hours At 5 °C 5-6 hours Product can be overcoated once cured and tack free. Maximum recoat period within 48 hours of application of primer. Above figures represent typical values though can be affected by on-site conditions
Notes on Application / Limitations	Do not apply in wet weather or to wet surfaces. Take care to ensure an even coverage and avoid ponding in voids and depressions.

Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Pakistan (Pvt) Limited
141-CCA, Phase IV, DHA
Lahore
Pakistan
Phone: +92 42 35694266-7
Fax: +92 42 35694268
information@pk.sika.com2
pak.sika.com

