

PRODUCT DATA SHEET

S-Felt A-300

Polypropylene levelling layer

DESCRIPTION

S-Felt A-300 is a levelling layer made of polypropylene (PP).

USES

- Levelling layer between Sarnafil® or Sikaplan® membranes and rough surfaces.

CHARACTERISTICS / ADVANTAGES

- Bitumen resistant
- Easily applied
- Recyclable (Delete if recycling facilities or recycling offerings are not available in local country)



PRODUCT INFORMATION

Chemical Base	100% polypropylene (PP)	
Packaging	Rolls wrapped individually in a black PE-foil.	
	Length	50,00 m
	Width	2,00 m
	Weight	30,00 kg
Appearance / Colour	Surface	Structured
	Colour	Multi-coloured
Shelf Life	5 years from date of production.	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Always refer to packaging.	
Length	50,00 m	

Width	2,00 m (+/- 2 %)	
Thickness	1,9 mm (+/- 10 %)	(EN 9863)
Mass per Unit Area	300 g/m ² (+/- 10 %)	(EN 9864)

TECHNICAL INFORMATION

Tensile Strength	longitudinal	≥ 300 N/50 mm	(EN 10319)
	transversal	≥ 400 N/50 mm	
Elongation	longitudinal	≤ 75 %	(EN 10319)
	transversal	≤ 75 %	
Reaction to Fire	Class E		(EN 13501-1)

SYSTEM INFORMATION

System Structure	The following products must be considered for use depending on roof design: <ul style="list-style-type: none"> ▪ All types of Sarnafil® and Sikaplan® membranes ▪ Sarnacol®-2170 ▪ Sarnacol® T-660
------------------	---

APPLICATION INFORMATION

Ambient Air Temperature	-20 °C min. / +60 °C max.
Substrate Temperature	-30 °C min. / +60 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- Do not use for permanent exposure to UV radiation.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above + 5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below + 5°C ambient temperature due to safety requirements in accordance with national regulations.

ECOLOGY HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

APPLICATION INSTRUCTIONS

APPLICATION

S-Felt A-300 is loose laid accordance with installation instructions: Sarnafil® and Sikaplan®.

If necessary S-Felt A-300 can be spot bonded to the substrate with Sarnacol®-2170 or Sarnacol® T-660.

Adjoining sheets must overlap at least 50 mm.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Pakistan (Pvt.) Limited

141-CCA Phase IV, DHA

Lahore Punjab 54792

Pakistan

phone: +92 42 3569 4266 - 67

fax: +92 42 3569 4268

<http://pak.sika.com/>

PRODUCT DATA SHEET

S-Felt A-300

May 2021, Version 01.01

020945051050000003

S-FeltA-300-en-PK-(05-2021)-1-1.pdf