

PRODUCT DATA SHEET

Sika® Plastiretard TM 100 C2 RET PK

Set retarding admixture for concrete

DESCRIPTION

Sika® Plastiretard TM 100 C2 RET PK is a liquid admixture developed for the control of cement hydration. Sika® Plastiretard TM 100 C2 RET PK retards and stabilizes concrete mixes without negatively influencing their final strength.

USES

Sika® Plastiretard TM 100 C2 RET PK retards the initial set in concrete to allow an extended period of workability.

CHARACTERISTICS / ADVANTAGES

Sika® Plastiretard TM 100 C2 RET PK retards the hydration of cement.

- Strong retardation to facilitate long haulage duration
- High resistance to segregation with reduced bleed
- Extended workability

PRODUCT INFORMATION

Chemical Base	Organic polymer blend
Packaging	05 ltr jerry can 20 ltr plastic can 200 ltr drum 1000 ltr IBC Bulk supply in tanker is possible on demand
Appearance / Colour	Brown Liquid
Shelf Life	12 months from date of production if stored properly in undamaged unopened, original sealed packaging.
Storage Conditions	The product must be stored properly in undamaged, unopened original sealed packaging in dry conditions at temperatures between +5° C and +35° C. Protect from direct sunlight and frost.
pH-Value	≥ 6
Total Chloride Ion Content	Nil as per EN934-2
Specific gravity	1.16 ± 0.03
Recommended Dosage	0.2–2.0 % by weight of cement. For additional dosage ranges; onsite trials are recommended.
Dispensing	Sika® Plastiretard TM 100 C2 RET PK should be dispensed through suitably calibrated dosing equipment.

Compatibility

Sika® Plastiretard TM 100 C2 RET PK should not be mixed directly with the following admixtures prior to dispensing as solids can form in the mixture. This can cause increased viscosity and pump / pipe blockages:

- Sika® Plastiment®-190
- SikaRapid®-1
- SikaRapid®-800 ECO
- Sika® Viscoflow®-1000
- Sika® Viscoflow®-2000

Important: Always conduct trials before combining products in specific mixes and contact our Technical Service Department for information and advice about any specific combinations.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

- The standard rules of good concreting practice, concerning production and placing, are to be followed.
- Laboratory trials shall be carried out before concreting on site, especially when using a new mix design or producing new concrete components.
- Fresh concrete must be cured properly and curing applied as early as possible.
- Sika® Plastiretard TM 100 C2 RET PK shall not be added to dry cement.
- Overdosing will result in an increase in setting time.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Pakistan (Pvt.) Limited

141-CCA Phase IV, DHA
Lahore Punjab 54792
Pakistan
phone: +92 42 3569 4266 - 67
fax: +92 42 3569 4268
<http://pak.sika.com/>

Sika Pakistan (Pvt.) Limited

141-CCA Phase IV, DHA
Lahore Punjab 54792
Pakistan
phone: +92 42 3569 4266 - 67
fax: +92 42 3569 4268
<http://pak.sika.com/>

Product Data Sheet

Sika® Plastiretard TM 100 C2 RET PK
August 2026, Version 01.01
021406011000247612

SikaPlastiretardTM100C2RETPK-en-PK-(08-2026)-1-1.pdf